

## PATTERN / MODEL / LAYING PATTERN

<b>COLLECTION</b>	FOREST
Pattern	Trees
Wood Species	European Oak
Grade	Elegant / Standard
Surface Machining	Sanded / Brushed / Handscraped / Sawn Brushed
Finish	Oiled
Constructions	multi-layered engineered parquet
Size	19/4 x 230 - 320 x 3000 - 5000 mm
Joint	T&G
Installation type	Full surface glued down
Underfloor Water Heating	Suitable*



\*read installation instructions - underfloor heating protocol

## BILL OF MATERIAL

(measurements in mm)



## CONSTRUCTION

<b>DIMENSIONS</b>	
Thickness	19 mm
Width	230 - 320 mm
Length	3000 - 5000 mm
Toplayer thickness	4 mm
Top layer construction	Solid wood (European Oak)
Core thickness	11 mm
Core construction	Plywood (Birch)
Microbevel	0,3 mm
Joint type	Tongue and Groove (T&G)

<b>PACKAGING</b>	BOX
Content	Custom pcs
Area content	Custom m <sup>2</sup>
Weight	Custom kg
H x W x L	Custom mm

## STORAGE AND USAGE



- Air humidity 45 % - 60 %
- Floor temperature +20 ° - +22 °
- Air temperature 18 ° - 24 °

## FINISH

### SANDED

Smooth surface, sanded and protected with oil, preserving the natural appearance of wood.

### BRUSHED

Soft wood removed from the surface with brush rollers so that only hard wood remains. The surface is harder and more resistant to scratches and impacts.

### HANDSCRAPED

Slightly wavy surface. Boards are protected with oil, maintaining the authentic, rustic appearance of wood.

### SAWN BRUSHED

Emphasized natural wood texture, protected with oil. Significantly increased durability and resilience.



